

WAC LIGHTING

7"/11"/15" Round

Ceiling and Wall Mount

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-07RN 7"	930 3000K - 90	15W	1100	BK Black
FM-11RN 11"	935 3500K - 90	15W	1100	BN Brushed Nickel
FM-15RN 15"	930 3000K - 90	20W	1525	BZ Bronze
	935 3500K - 90	20W	1525	WT White
	930 3000K - 90	28W	2550	
	935 3500K - 90	28W	2550	

QTY: 1
LOCATION: BED 1 WIC

Example: **FM-07RN-930-BK** **FM-11RN-930-WT**

FEATURES

- Multiple LED array for uniform illumination
- Driver installed within the Junction Box, driver dimension: 2.25" dia x 1" deep
- 5 year warranty

SPECIFICATIONS

Construction	Aluminum with translucent diffuser
Power:	15W, 20W, 28W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: Electroplated Brushed Nickel, Black, Bronze, White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, ADA, Title 24 JA8 Compliant



not pancake box compatible

FINISHES:



LINE DRAWING

